

Fast assembly concealed hinge

- ▶ **Intermat 9930 for corner cabinet folding doors**
- ▶ **Opening angle 50° / 65°**



- ▶ Concealed hinge with clip on assembly
- ▶ Quality classification under EN 15570, Level 2
- ▶ Cup diameter 35 mm
- ▶ Cup depth 11.1 mm (Fix 11.6 mm)
- ▶ Diagonal adjustment + 9.5 mm / - 9.5 mm
- ▶ Integrated overlay adjustment, see diagram
- ▶ For integrated depth adjustment, see diagram
- ▶ Height adjustment at mounting plate
- ▶ Hinge arm material: zinc die-cast nickel plated
- ▶ Hinge cup material: steel, nickel plated

Intermat 9930, opening angle 50° / 65°

overlay

Base B 24 mm

PU

Cup assembly	Drilling pattern	Mounting drilling ø x T mm	Base B 24 mm	PU
For screwing on TH 42		-	0 045 036	1/50 ea.
For pressing in TH 43		ø 10 x 11	0 045 037	1/50 ea.
Flash fast assembly TH 44		ø 10 x 11	0 045 039	1/50 ea.
Fix fast assembly TH 45		ø 10 x 6	0 045 042	1/50 ea.
For pressing in TB 43		ø 8 x 11	0 045 038	1/50 ea.
Fix fast assembly TB 45		ø 8 x 6	0 045 043	1/50 ea.