


- ▶ System 8099 mounting plates with eccentric cam height adjustment
- ▶ For Sensys


## Cross mounting plate with premounted chipboard screws



- ▶ For drillings max.  $\varnothing$  2.5 mm
- ▶ Quality classification under EN 15570, Level 3
- ▶ Hole spacing 32 mm
- ▶ Eccentric cam height adjustment  $\pm$  2 mm
- ▶ Steel, nickel plated

Hole line distance	Order no. / distance mm				PU
	0.0	1.5	3.0	5.0	
37	9 075 085	9 075 086	9 075 087	9 075 088	1/50 ea.
37	9 071 670	9 071 671	9 071 672	9 071 673	200 ea.


## Cross mounting plate with premounted Euro screws



- ▶ For  $\varnothing$  5 x 12 mm drillings
- ▶ Quality classification under EN 15570, Level 3
- ▶ Hole spacing 32 mm
- ▶ Eccentric cam height adjustment  $\pm$  2 mm
- ▶ Steel, nickel plated

Hole line distance	Order no. / distance mm				PU
	0.0	1.5	3.0	5.0	
37	9 075 080	9 075 081	9 075 082	9 075 083	1/50 ea.
37	9 071 665	9 071 666	9 071 667	9 071 668	200 ea.

## Cross mounting plate with premounted Euro screws



- ▶ For  $\varnothing$  5 x 8 mm drillings
- ▶ Quality classification under EN 15570, Level 3
- ▶ Hole spacing 32 mm
- ▶ Half overlay door, from 16 mm side panel thickness
- ▶ Eccentric cam height adjustment  $\pm$  2 mm
- ▶ Steel, nickel plated

Hole line distance	Order no. / distance mm				PU
	0.0	1.5	3.0	5.0	
37	9 075 060	9 075 061	9 075 062	9 075 063	1/50 ea.
37	9 071 645	9 071 646	9 071 647	9 071 648	200 ea.