


Fast assembly concealed hinge

- ▶ System 8099 mounting plates with eccentric cam height adjustment
- ▶ For Sensys


Cross mounting plate for pressing in



- ▶ For ø 10 x 12 mm drillings
- ▶ Quality classification under EN 15570, Level 3
- ▶ Hole spacing 32 mm
- ▶ Eccentric cam height adjustment ± 2 mm
- ▶ Steel, nickel plated

Hole line distance	Order no. / distance mm				PU
	0.0	1.5	3.0	5.0	
37	9 075 090	9 075 091	9 075 092	9 075 093	1/50 ea.
37	9 071 680	9 071 681	9 071 682	9 071 683	200 ea.


Cross mounting plate with expanding sockets and special screws



- ▶ For ø 10 x 12 mm drillings
- ▶ Quality classification under EN 15570, Level 3
- ▶ Hole spacing 32 mm
- ▶ Eccentric cam height adjustment ± 2 mm
- ▶ Steel, nickel plated

Hole line distance	Order no. / distance mm				PU
	0.0	1.5	3.0	5.0	
37	9 075 075	9 075 076	9 075 077	9 075 078	1/50 ea.
37	9 071 660	9 071 661	9 071 662	9 071 663	200 ea.

Cross mounting plate with expanding sockets and special screws



- ▶ For ø 5 x 12 mm drillings
- ▶ Quality classification under EN 15570, Level 3
- ▶ Hole spacing 32 mm
- ▶ Eccentric cam height adjustment ± 2 mm
- ▶ Steel, nickel plated

Hole line distance	Order no. / distance mm				PU
	0.0	1.5	3.0	5.0	
37	9 075 070	9 075 071	9 075 072	9 075 073	1/50 ea.
37	9 071 655	9 071 656	9 071 657	9 071 658	200 ea.